D-Link®

mydlink™

360º
360° View
Pan & Tilt

2K QHD Pan & Tilt Wi-Fi Camera

(DCS-8526LH)

Smarter Camera, Safer Home

- 2K QHD 1440P resolution
- Dual-band (2.4 GHz / 5 GHz) Wi-Fi connectivity
- Built-in Bluetooth Low Energy 5.0 technology for faster setup
- WPA3™ and TLS encryption for enhanced protection
- AI-based algorithm intelligently detects human motion
- Color night vision enables clear full-color video even in low light, and IR night vision lets you see up to 7M (23 ft.) in total darkness
- Two-way audio with built-in microphone and speaker
- Carbon Monoxide (CO) and smoke alarm sound detection
- Ethernet port for wired connection
- Continuous recording[1] to local microSD[2]
- Connect to ONVIF-compatible NAS/NVR/VMS for local recording
- Access anytime, anywhere with the free mydlink app
- Voice control works with Amazon Alexa or Google Assistant

works with **Google** Home

works with **alexa**

2K QHD Quality
True 2K QHD 1440P resolution for superior live video clarity

Wireless/Ethernet Connectivity
Wireless 2.4 GHz and 5 GHz with optional wired Ethernet connectivity

Panorama View Angle Selection
See the camera's range of view and tap to jump to a specific area

AI-Based Person Detection
Advanced algorithm Intelligently identifies human motion

Auto Motion Tracking
Automatically pans and tilts to follow an object as it moves

Two-Way Audio
Transmit and receive audio with built-in microphone and speaker

CO/Smoke Alarm Detection
Alerts you when carbon monoxide and smoke alarms are detected

Voice Assistants
Voice control works with Amazon Alexa or Google Assistant

Camera

Hardware Profile	• 1/3" Progressive CMOS sensor
	• 7 m (23 ft) IR illumination distance
	• Built-in Infrared-Cut Removable (ICR) Filter module
	• Focal length 3.18 mm
	• Aperture F1.6
		• Angle of view (16:9):
		  • Horizontal: 102.5°
		  • Vertical: 55.2°
		  • Diagonal: 122°
		• Built-in microphone and speaker

Video Resolution	Max. resolution: 1440p (2560 x 1440)	
Video Compression	H.265 / H.264 format compression	
Audio Support	MPEG-2 AAC LC	
Image Features	• Configurable image size	• Person detection

Pan/Tilt

Pan Range	-170° to +170° (total 340°)
Tilt Range	-15° to +90° (total 105°)

Network

Connectivity	• 802.11n/ac wireless • Wi-Fi operates on 2.4 GHz and 5 GHz bands	• 10 /100 Base-TX Ethernet (RJ-45) • Bluetooth Low Energy 5.0
Network Protocols	• IPv4/IPv6	• DHCP/DHCPv6 Client
Security Protocol	• WPA3	• TLS

System Management

Event Management	• Person detection • Push notifications • Motion detection • CO/smoke alarm sound detection[5]	• Sound detection • microSD card recording • mydlink Cloud recording[3]
Device Management	• mydlink app[4] (iOS and Android)	• mydlink portal

Physical

Environment	For indoor use only	
Weight	320 g (11.3 oz)	
Power Adapter	• Input: 100 to 240 V AC, 50/60 Hz	• Output: 5 V DC 2.0 A (Type C)
Temperature	• Operating: 0 to 40 °C (32 to 104 °F)	• Storage: -20 to 70˚ C (-4 to 158 ˚F)
Humidity	• Operating: 20% to 90% non-condensing	• Storage: 5% to 90% non-condensing
Dimensions (L x W x H)	77.89 x 77.70 x 114.12 mm (3.1 x 3.1 x 4.5 in)	
Certifications	• FCC	• CE
Hardware Version	B1	

[1] Use of audio or video equipment for recording the image or audio of a person without their knowledge and consent is prohibited in certain states or jurisdictions. The end-user assumes all liability for compliance with applicable state, local and federal laws.
[2] microSD card not included. Supports capacity up to 256GB.
[3] Minimum recommended upload bandwidth of 2.5 Mbps for live viewing or 5 Mbps for cloud recording.
[4] Please refer to the app's store page to check whether your device is compatible.
[5] CO/Smoke Alarm Sound Detection accuracy may be influenced by multiple factors and should not be relied upon in circumstances where there is any risk of injury to yourself or others, or in emergencies and other high-risk situations.

Status LED

IR LEDs

2K QHD 1440p Resolution Lens

Light Sensor

microSD Card Slot

Microphone

Speaker

Reset

Ethernet Port

Power Connector

D-Link®

B1 v1.01 WW