

Product Highlights

High Performance

Gigabit access ports and built-in 10 Gigabit uplinks provide high bandwidth connections for clients, servers, and storage

Flexible Software

Multiple software images provide a flexible approach to software management, allowing only the required features to be installed

High Availability

Up to 9 physical switches can be stacked to create a single virtual switch, providing fault tolerance and increasing network reliability



DGS-3630 Series

Layer 3 Stackable Managed Switches

Features

High Availability and Flexibility

- 20/44 10/100/1000BASE-T ports or 20 SFP ports
- 4 Combo 10/100/1000BASE-T/SFP ports
- 4 10 GbE SFP+ uplink ports
- Switch Resource Management (SRM) for flexible management of system resources
- 6 kV surge protection on all RJ-45 access ports
- IEEE 802.3af/at PoE (DGS-3630-28PC/52PC)

Reliability

- Redundant Power Supply (RPS) support
- IEEE 802.1D/802.1w/802.1s Spanning Tree
- Loopback Detection (LBD)
- Ethernet Ring Protection Switching (ERPS)

High Bandwidth Stacking

- Physical stack of up to 9 units, 432 GbE ports
- Supports long-distance stacking over fiber
- 80 Gbps per device physical stacking bandwidth

Operations, Administration, and Maintenance

- IEEE 802.3ah Ethernet Link OAM
- IEEE 802.1ag/ITU-T Y.1731 Service OAM

Easy Management

- RJ-45/mini-USB console port
- Management and alarm ports
- USB port for firmware and configuration files
- Easy-to-use web GUI and industry-standard CLI

The DGS-3630 Series Layer 3 Stackable Managed Switches are designed for Small to Medium-sized Businesses (SMBs), Small to Medium-sized Enterprises (SMEs), large enterprises, and Internet Service Providers (ISPs). They deliver high performance, flexibility, fault tolerance, and advanced software features for maximum return on investment. With Gigabit Ethernet, SFP, 10 Gigabit SFP+, security features, and advanced Quality of Service (QoS), the DGS-3630 Series can act as core, distribution, or access layer switches. High port density, switch stacking, and easy management make the DGS-3630 Series suitable for a variety of applications.

Standard, Enhanced, and MPLS Images

The DGS-3630 Series is designed for use with three different software images: the Standard Image (SI), the Enhanced Image (EI), and the MPLS Image (MI)¹. The Standard Image provides core SMB and SME functionality such as L2 switching, entry-level routing, L2 multicast, advanced QoS, Operations, Administration, and Maintenance (OAM), and robust security features. The Enhanced Image supports all the features of the Standard Image in addition to full L3 routing for enterprise integration, including OSPF, BGP, VRF-Lite and L3 multicast. The MPLS Image offers all the features of the Standard and Enhanced Images in addition to VPN services for ISPs, including IS-IS and MPLS L2/L3 VPN. With multiple software images, only the required features need to be installed, providing a flexible approach to software management.

High Availability and Flexibility

The DGS-3630 Series allows multiple switches to be combined to form a single physical² or virtual stack. This increases redundancy over multiple physical units, simplifies management, and provides a single IP address to manage all members in the stack. Up to 9 switches can be combined using DACs to make up to 432 Gigabit Ethernet ports available, allowing switching capacity to be increased with demand. The Switch Resource Management (SRM) feature allows the hardware table size to be dynamically changed, so that switch functions can be optimized based on the use of the switch. There are 3 modes: IP Mode, LAN Mode, and L2 VPN Mode. These modes modify the size of the Layer 2 and 3 tables for optimum efficiency.

Switch and Link Failover

In addition to traditional Spanning Tree Protocol (STP), Rapid Spanning Tree Protocol (RSTP), and Multiple Spanning Tree Protocol (MSTP), the DGS-3630 Series also supports advanced Ethernet failover redundancy technologies, such as ERPS and FlexLink. Ethernet Ring Protection Switching (ERPS) provides millisecond-level failover in a ring topology. Meanwhile, FlexLink offers link failover on designated switch ports, providing link redundancy without STP or LBD.

Security, Performance, and Availability

The DGS-3630 Series provides a complete set of security features including multi-layer Access Control Lists (ACLs) and 802.1X user authentication via TACACS+ and RADIUS. The DGS-3630 Series also offers extensive VLAN support, including GVRP and 802.1Q VLAN to enhance security and performance. A robust set of QoS features help ensure that critical network services such as Voice over IP and video conferences are given high priority through the network. The D-Link Safeguard Engine increases the switches' reliability, serviceability, and availability by preventing traffic flooding caused by malicious attacks.

Versatile Management

The DGS-3630 Series provides the D-Link Network Assistant (DNA) utility, an industry-standard CLI, and an intuitive web-based management interface that enables administrators to set up and remotely manage their networks. Support for SNMP allows centralized management of a large number of devices and out-of-band management is available via a dedicated console port. A mini-USB console port allows the DGS-3630 Series to be managed without any extra connectors, and a USB Type A port can be used to connect a storage device to store logs, configuration settings, and firmware images. The DHCP auto-configuration and auto-image features enable deployment of multiple switches automatically, saving costs for mass deployment. The DGS-3630 Series furthermore integrates essential features of OpenFlow 1.3, allowing the switches to be managed using an OpenFlow controller^{6,7}.

Power over Ethernet (PoE) Support

The DGS-3630-28PC and DGS-3630-52PC models feature Power over Ethernet, which allows PoE-powered devices to be powered by the switch through a standard Ethernet cable. Both models support the IEEE 802.3af PoE and IEEE 802.3at PoE+ standards, providing up to 30 W of power per port. PoE effectively reduces deployment time for PoE devices such as IP cameras, VoIP phones, and access points, and eliminates the cost for additional electrical cabling. Both models feature a 370 W PoE power budget which can be increased to 740 W when outfitted with the DPS-700 redundant power supply, allowing the switches to power even more devices. Additionally, an extended Link Layer Discovery Protocol (LLDP) automatically negotiates and manages the power feed to IEEE 802.3at PoE+ powered devices for optimal power distribution.

6 kV Surge Protection

The DGS-3630 Series features built-in 6 kV surge protection on all PoE and non-PoE Ethernet access ports, and requires no external surge protection devices. This effectively protects the switches against sudden electrical surges caused by events such as lightning strikes or unstable electrical current. Built-in 6 kV surge protection significantly reduces the chance of equipment being damaged from electrical surges, and effectively lowers maintenance costs by minimizing the need for expensive equipment repairs or replacement.

D-Link Green Technology

The DGS-3630 Series features D-Link Green technology, which includes a power-saving mode, smart fan feature, reduced heat dissipation, and cable length detection. The power-saving feature automatically powers down ports that have no link or link partner, and ensures that LEDs are shut off when not needed. The smart fan³ feature enables the built-in fans to automatically activate above a certain temperature threshold, providing continuous, reliable, and eco-friendly operation of the switch.

Technical Specifications

General	DGS-3630-28SC	DGS-3630-28TC	DGS-3630-52TC
Size	• 19-inch, 1U rack-mount size		
Interfaces	<ul style="list-style-type: none"> • 20 x SFP ports • 4 x Combo 10/100/1000BASE-T/SFP ports • 4 x 10 GbE SFP+ ports 	<ul style="list-style-type: none"> • 20 x 10/100/1000BASE-T ports • 4 x Combo 10/100/1000BASE-T/SFP ports • 4 x 10 GbE SFP+ ports 	<ul style="list-style-type: none"> • 44 x 10/100/1000BASE-T ports • 4 x Combo 10/100/1000BASE-T/SFP ports • 4 x 10 GbE SFP+ ports
Console Port	• RJ-45 and Mini-USB console ports for out-of-band CLI management		
Management Port	• 10/100/1000BASE-T RJ-45 Ethernet port for out-of-band IP management		
Alarm Port	• 1 x RJ-45 port		
USB Port	• 1 x USB 2.0 Type A port		

Performance			
Switching Capacity	• 128 Gbps	• 128 Gbps	• 176 Gbps
Packet Forwarding Rate	• 95.24 Mpps	• 95.24 Mpps	• 130.95 Mpps
Packet Buffer	• 4 MBytes		
MAC Address Table	• 68K entries ⁴		
IPv4 Routing Table	• 16K entries		
IPv6 Routing Table	• 7K entries		
IPv4 Forwarding Table	• 32K entries ⁴		
IPv6 Forwarding Table	• 16K entries ⁴		
Jumbo Frame Size	• 12 KBytes		
Physical			
MTBF	• 280,612.09 hours	• 300,190.46 hours	• 263,936.78 hours
Acoustics	• 56 dB(A)	• 52.7 dB(A)	• 53.9 dB(A)
Heat Dissipation	• 216.81 BTU/h	• 144.58 BTU/h	• 212 BTU/h
Power Input	• 100 to 240 VAC 50/60 Hz		
Maximum Power Consumption	• 63.58 W	• 42.4 W	• 62 W
Standby Power Consumption	• 30.1 W	• 28.1 W	• 36 W
Dimensions	• 441 x 259.8 x 44 mm (17.4 x 10.2 x 1.73 in)		
Weight	• 3.79 kg (8.36 lbs)	• 3.74 kg (8.25 lbs)	• 4.04 kg (8.91 lbs)
Ventilation	• 2 x smart fans ³		
Operating Temperature	• -5 to 50 °C (23 to 122 °F)		
Storage Temperature	• -40 to 70 °C (-40 to 158 °F)		
Operating Humidity	• 10% to 95% RH		
Storage Humidity	• 5% to 95% RH		
Surge Protection	• 6 kV surge protection on all Ethernet access ports		
Safety Certifications	• cUL, CB, CE, CCC, BSMI		
EMI/EMC	• CE, FCC Class A, C-Tick, VCCI, BSMI, CCC		
IPv6 Ready Certification	• IPv6 Ready Logo Phase-2		

Technical Specifications

General	DGS-3630-28PC	DGS-3630-52PC
Size	• 19-inch, 1U rack-mount size	
Interfaces	<ul style="list-style-type: none"> • 20 x 10/100/1000BASE-T PoE ports • 4 x Combo 10/100/1000BASE-T PoE/SFP ports • 4 x 10 GbE SFP+ ports 	<ul style="list-style-type: none"> • 44 x 10/100/1000BASE-T PoE ports • 4 x Combo 10/100/1000BASE-T PoE/SFP ports • 4 x 10 GbE SFP+ ports
Console Port	• RJ-45 and Mini-USB console ports for out-of-band CLI management	
Management Port	• 10/100/1000BASE-T RJ-45 Ethernet port for out-of-band IP management	
Alarm Port	• 1 x RJ-45 port	
USB Port	• 1 x USB 2.0 Type A port	
Performance		
Switching Capacity	• 128 Gbps	• 176 Gbps
Packet Forwarding Rate	• 95.24 Mpps	• 130.95 Mpps
Packet Buffer	• 4 MBytes	
MAC Address Table	• 68K entries ⁴	
IPv4 Routing Table	• 16K entries	
IPv6 Routing Table	• 7K entries	
IPv4 Forwarding Table	• 32K entries ⁴	
IPv6 Forwarding Table	• 16K entries ⁴	
Jumbo Frame Size	• 12 KBytes	
Power over Ethernet (PoE)		
PoE Standards	• IEEE 802.3af/at	
PoE Power Budget	• 370 W (740 W with DPS-700 RPS redundant power supply)	
Physical		
MTBF	• 259,222.76 hours	• 199,929.76 hours
Acoustics	• 48.2 dB(A)	• 51.9 dB(A)
Heat Dissipation	• 1600.31 BTU/h	• 1653.85 BTU/h
Power Input	• 100 to 240 VAC 50/60 Hz	
Maximum Power Consumption	<ul style="list-style-type: none"> • PoE off: 44.3 W • PoE on: 469.3 W 	<ul style="list-style-type: none"> • PoE off: 54.1 W • PoE on: 485 W
Standby Power Consumption	• 34.6 W	• 44.6 W
Dimensions	• 441 x 380 x 44 mm (17.4 x 15 x 1.73 in)	
Weight	• 5.88 kg (12.96 lbs)	• 6.30 kg (13.89 lbs)
Ventilation	• 4 x smart fans ³	
Operating Temperature	• -5 to 50 °C (23 to 122 °F)	
Storage Temperature	• -40 to 70 °C (-40 to 158 °F)	

Operating Humidity	• 10% to 95% RH
Storage Humidity	• 5% to 95% RH
Surge Protection	• 6 kV surge protection on all Ethernet access ports
Safety Certifications	• cUL, CB, CE, CCC, BSMI
EMI/EMC	• CE, FCC Class A, C-Tick, VCCI, BSMI, CCC

Standard Image Software Features		
Stackability	<ul style="list-style-type: none"> Physical stacking <ul style="list-style-type: none"> Up to 80 Gbps stacking bandwidth Up to 9 switches in a stack Ring/chain topology support 	<ul style="list-style-type: none"> Virtual stacking/clustering of up to 32 units <ul style="list-style-type: none"> Supports D-Link Single IP Management Up to 20 Gbps stacking bandwidth
L2 Features	<ul style="list-style-type: none"> MAC Address Table : up to 68K entries⁴ Flow Control <ul style="list-style-type: none"> 802.3x Flow Control when using full-duplex for port speed HOL Blocking Prevention Spanning Tree Protocol <ul style="list-style-type: none"> 802.1D STP 802.1w RSTP 802.1s MSTP Root Guard Loop Guard Jumbo Frame: up to 12 KBytes 802.1AX Link Aggregation <ul style="list-style-type: none"> Max. 32 groups per device, 8 ports per group 	<ul style="list-style-type: none"> ERPS (Ethernet Ring Protection Switching) version 2 Port Mirroring <ul style="list-style-type: none"> Supports One-to-One, Many-to-One, Supports Mirroring for Tx/Rx/Both Supports 4 mirroring groups Flow Mirroring <ul style="list-style-type: none"> Supports Mirroring for Rx VLAN Mirroring RSPAN L2 Protocol Tunneling Multi-Chassis Link Aggregation Group (MLAG)⁶
VLAN	<ul style="list-style-type: none"> 802.1Q 802.1v Protocol-based VLAN Double VLAN (Q-in-Q) <ul style="list-style-type: none"> Port-based Q-in-Q Selective Q-in-Q Port-based VLAN MAC-based VLAN Subnet-based VLAN Private VLAN 	<ul style="list-style-type: none"> VLAN Group <ul style="list-style-type: none"> Max. 4K VLAN groups Max. 4094 VIDs Multicast VLAN (ISM VLAN for IPv4/IPv6) Voice VLAN Auto Surveillance VLAN VLAN Trunking GVRP: Up to 4K dynamic VLANs Asymmetric VLAN
L2 Multicast	<ul style="list-style-type: none"> MLD Snooping <ul style="list-style-type: none"> MLD v1/v2 Snooping Supports up to 4K MLD groups⁴ Host-based MLD Snooping Fast Leave Supports 64 static MLD groups MLD Snooping Querier <ul style="list-style-type: none"> Per VLAN MLD Snooping MLD Proxy Reporting 802.1ak MVRP⁸ 	<ul style="list-style-type: none"> IGMP Snooping <ul style="list-style-type: none"> IGMP v1/v2/v3 Supports up to 8K IGMP groups⁴ Supports 64 static IGMP groups Per VLAN IGMP Snooping IGMP Snooping Querier <ul style="list-style-type: none"> Host-based IGMP Snooping Fast Leave PIM Snooping
L3 Features	<ul style="list-style-type: none"> IPv4 ARP/IPv6 ND: support up to 32K/16K⁴ <ul style="list-style-type: none"> 512 Static ARP Gratuitous ARP IP Interface <ul style="list-style-type: none"> Supports 256 interfaces Loopback Interface Proxy ARP <ul style="list-style-type: none"> Support local ARP proxy 	<ul style="list-style-type: none"> IPv6 Tunneling <ul style="list-style-type: none"> Static ISATAP GRE <ul style="list-style-type: none"> 6to4 VRRP v2/v3 IP Helper
L3 Routing	<ul style="list-style-type: none"> Supports 16K hardware routing entries shared by IPv4/IPv6 <ul style="list-style-type: none"> 1 entry consumed by each IPv4 route 2 entries consumed by each IPv6 route Supports up to 32K hardware L3 forwarding entries shared by IPv4/IPv6⁴ <ul style="list-style-type: none"> 1 entry consumed by each IPv4 route 2 entries consumed by each IPv6 route Static Route <ul style="list-style-type: none"> Max. 512 IPv4 entries Max. 256 IPv6 entries IPv4/IPv6 Default Route 	<ul style="list-style-type: none"> PBR (Policy-based Route) Null Route Route Preference Route Redistribution Graceful Restart (GR) Helper BFD (Bidirectional Forwarding Detection) <ul style="list-style-type: none"> IPv4/v6 Static Route RIP VRRP OSPFv3⁸ BGPv4⁸ RIPv1/v2/ng
L3 Multicast	<ul style="list-style-type: none"> IGMP/MLD Filtering 	

Standard Image Software Features (Continued)

<p>QoS (Quality of Service)</p>	<ul style="list-style-type: none"> • 802.1p • 8 queues per port • Queue Handling <ul style="list-style-type: none"> • Strict Priority (SP) • Weighted Round Robin (WRR) • Strict + WRR • Weighted Deficit Round Robin (WDRR) • Congestion Control <ul style="list-style-type: none"> • Weighted Random Early Detection (WRED) • 802.1Qbb Priority-based Flow Control (PFC) for 10 GbE port • Bandwidth Control <ul style="list-style-type: none"> • Port-based (ingress/egress, min. granularity 8 Kb/s) • Flow-based (ingress/egress, min. granularity 8 Kb/s) • Per queue bandwidth control (min. granularity 8 Kb/s) • Policy Map <ul style="list-style-type: none"> • Remark 802.1p priority • Remark IP precedence/DSCP • Time based QoS 	<ul style="list-style-type: none"> • CoS based on: <ul style="list-style-type: none"> • Switch port • Inner/outer 802.1p Priority • Inner/outer VID • MAC address • Ether Type • IP address • ToS/IP Preference • DSCP • Protocol type • TCP/UDP port • IPv6 Traffic Class • IPv6 Flow Label • Three Color Marker <ul style="list-style-type: none"> • trTCM • srTCM
<p>ACL (Access Control List)</p>	<ul style="list-style-type: none"> • ACL based on: <ul style="list-style-type: none"> • 802.1p priority • VID • MAC address • Ether Type • LLC • VLAN • IP address • IP preference/ToS • DSCP mask • Protocol type • TCP/UDP port number • IPv6 Traffic Class • IPv6 Flow Label 	<ul style="list-style-type: none"> • Max. ACL entries: <ul style="list-style-type: none"> • Ingress (hardware entries): 4K • Egress (hardware entries): 1K • VLAN Access Map Numbers: 3K • Time-based ACL
<p>Green</p>	<ul style="list-style-type: none"> • Energy-Efficient Ethernet (EEE) • Power saving by link status • Power saving by cable length • Time-based PoE (PoE models only) 	<ul style="list-style-type: none"> • Power saving by LED shut-off • Power saving by port shut-off • Power saving by system hibernation
<p>Security</p>	<ul style="list-style-type: none"> • Port Security <ul style="list-style-type: none"> • Supports up to 12K MAC addresses per port/VLAN/system • Broadcast/Multicast/Unicast Storm Control • D-Link Safeguard Engine • DHCP Server Screening • Dynamic ARP Inspection • IP Source Guard • DHCP Snooping • IPv6 Snooping • Dynamic ARP Inspection (DAI) • DHCPv6 Guard • IPv6 Route Advertisement (RA) Guard • IPv6 ND Inspection • Duplicate Address Detection (DAD) 	<ul style="list-style-type: none"> • ARP Spoofing Prevention <ul style="list-style-type: none"> • Max. 64 entries • L3 Control Packet Filtering • Unicast Reverse Path Forwarding (URPF) • Traffic Segmentation • SSL <ul style="list-style-type: none"> • Supports TLS 1.0/1.1/1.2 • Supports IPv4/IPv6 access • SSH <ul style="list-style-type: none"> • Supports SSH v2 • Supports IPv4/IPv6 access • Supports Server/Client • BPDU Attack Prevention • DOS Attack Prevention • NetBIOS/NetBEUI filtering

Standard Image Software Features (Continued)

AAA	<ul style="list-style-type: none"> • 802.1X Authentication <ul style="list-style-type: none"> • Supports port/host-based access control • Identity-driven Policy Assignment • Dynamic VLAN Assignment • Bandwidth Control Assignment • ACL Assignment • Web-based Access Control (WAC) <ul style="list-style-type: none"> • Supports port/host-based access control • Identity-driven Policy Assignment • Dynamic VLAN Assignment • Bandwidth Control Assignment • ACL Assignment • Support IPv4/IPv6 access • Support HTTPS • Compound Authentication 	<ul style="list-style-type: none"> • MAC-based Access Control (MAC) <ul style="list-style-type: none"> • Supports port/host-based access control • Identity-driven Policy Assignment • Dynamic VLAN Assignment • Bandwidth Control Assignment • ACL Assignment • Guest VLAN • Microsoft[®] NAP <ul style="list-style-type: none"> • Support 802.1X NAP • Support DHCP NAP • Privilege Level for Management Access • RAIDUS and TACACS+ Authentication • Authentication Database Failover • RADIUS/TACACS+ Accounting • Japanese Web-based Access Control (JWAC)⁸ • RADIUS Change of Authorization (CoA)⁸ • RADIUS Filter Rule Attribute⁸
OAM (Operations, Administration, and Maintenance)	<ul style="list-style-type: none"> • Cable Diagnostics • 802.3ah Ethernet Link OAM • D-Link Unidirectional Link Detection (DULD) • Dying Gasp 	<ul style="list-style-type: none"> • 802.1ag Connectivity Fault Management (CFM) • Y.1731 OAM • Optical Transceiver Digital Diagnostic Monitoring (DDM)
Management	<ul style="list-style-type: none"> • NTPv3/v4 • Precision Time Protocol (PTP) <ul style="list-style-type: none"> • One-Step Clock • Boundary Clock Mode • Transparent Clock Mode • Web-based GUI <ul style="list-style-type: none"> • Support IPv4/IPv6 access • Support SSL (HTTPS) • Command Line Interface (CLI) • Telnet Server for IPv4/IPv6 access • Telnet Client for IPv4/IPv6 • SNMP <ul style="list-style-type: none"> • Support v1/v2c/v3 • Support IPv4/IPv6 access • SNMP Trap • TFTP Client for IPv4/IPv6 • FTP Client for IPv4/IPv6 • IPv4 SFTP Server • RCP • System Log for IPv4/IPv6 Syslog Server • SMTP • RMONv1 <ul style="list-style-type: none"> • Supports 1, 2, 3, 9 groups • RMONv2 <ul style="list-style-type: none"> • Supports ProbeConfig group • OpenFlow⁷ <ul style="list-style-type: none"> • Essential features of OpenFlow 1.3 • Single pipeline/flow table • Switch mode: Pure/Hybrid • Max flow rules: Pure Mode: 2048, Hybrid Mode: 1920 	<ul style="list-style-type: none"> • Command Logging • LLDP/LLDP-MED • D-Link Discover Protocol (DDP) • DHCP Client option 12 • DHCP Auto-configuration • DHCP Auto-image • DHCP Relay option 60/61/62/18/37/125 • DHCP/DHCPv6 Local Relay • DHCP Server <ul style="list-style-type: none"> • Support IPv4/IPv6 address assignment • DHCPv6 Prefix Delegation (PD) • Multiple Images/ Multiple Configurations • DNS Relay for IPv4/IPv6 • DNS Client for IPv4/IPv6 • Debug Command • Password recovery/ encryption • Ping/ Traceroute for IPv4/IPv6 • Microsoft[®] Network Load Balancing (NLB) • Switch Resource Management (SRM) • sFlow • D-Link License Management System (DLMS) • PD Alive (PoE models only)

Additional Enhanced Image (EI) Features	
VLAN	<ul style="list-style-type: none"> • Super VLAN
L3 Routing	<ul style="list-style-type: none"> • BGP <ul style="list-style-type: none"> • BGPv4/v4+ • 4bytes AS • Text/MD5 for BGPv4 • VRF-Lite <ul style="list-style-type: none"> • IPv4 Static Route • RIPv1/v2 • OSPFv2 • BGPv4 • Bidirectional Forwarding Detection (BFD) for OSPF • OSPF <ul style="list-style-type: none"> • OSPF v2/v3 • OSPF passive interface • Stub/NSSA area • OSPF equal cost route • Text/MD5 for OSPFv2
L3 Multicast	<ul style="list-style-type: none"> • IGMPv1/v2/v3 • MLDv1/v2 • IGMP/MLD Proxy • DVMRPv3 • PIM SDM (Sparse-Dense Mode)/SSM • PIM-SM/DM for IPv4/IPv6 • SSM Mapping for IPv4/IPv6 • Multicast Source Discovery Protocol (MSDP)
Additional MPLS Image (MI) Features	
L3 Routing	<ul style="list-style-type: none"> • IS-IS v4/v6
MPLS	<ul style="list-style-type: none"> • Label Distribution Protocol (LDP) • PHP (Penultimate hop popping) • Virtual Private Wire Service (VPWS) • Virtual Private LAN Service (VPLS) • BGP/MPLS VPN <ul style="list-style-type: none"> • Multiprotocol extensions for BGP4 • Virtual Routing Forwarding (VRF) • LSP/VCCV/MPLS Ping/Traceroute
MIB/IETF Standards	
	<ul style="list-style-type: none"> • RFC1065, RFC1066, RFC1155, RFC1156, RFC2578 MIB Structure • RFC1212 Concise MIB Definitions • RFC1213 MIBII • RFC1215 MIB Traps Convention • RFC1493, RFC4188 Bridge MIB • RFC1157, RFC2571, RFC2572, RFC2573, RFC2574, RFC2575, RFC2576 SNMP MIB • RFC1442, RFC1901, RFC1902, RFC1903, RFC1904, RFC1905, RFC1906, RFC1907, RFC1908, RFC2578, RFC3418, RFC3636 SNMPv2 MIB • RFC271, RFC1757, RFC2819 RMON MIB • RFC2021 RMONv2 MIB • RFC1398, RFC1643, RFC1650, RFC2358, RFC2665, RFC3635 Ether-like MIB • RFC2668 802.3 MAU MIB • RFC2674, RFC4363 802.1p MIB • Interface Group MIB • RFC2618 RADIUS Authentication Client MIB • RFC4022 MIB for TCP • RFC4113 MIB for UDP • RFC2620 RADIUS Accounting Client MIB • RFC2925 Ping & TRACEROUTE MIB • TFTP uploads and downloads (D-Link MIB) • Trap MIB (D-Link MIB) • RFC4293 IPv6 MIB • RFC4293 ICMPv6 MIB • Entity MIB • RIPv2 MIB • OSPF MIB • IPv4 Multicast Routing MIB • PIM MIB for IPv4 • IP Forwarding Table MIB • RFC4884 Extended ICMP to support Multi-Part Messages • RFC4293 IPv6 SNMP Mgmt Interface MIB • DDM MIB (D-Link MIB) • Private MIB • MIB for D-Link Zone Defense • DDP MIB • LLDP-MED MIB • RFC791 IP • RFC768 UDP • RFC793 TCP • RFC792 ICMPv4 • RFC2463, RFC4443 ICMPv6 • RFC826 ARP • RFC1338, RFC1519 CIDR • RFC2474, RFC3168, RFC3260 Definition of the DS Field in the IPv4 and IPv6 Headers • RFC1321, RFC2284, RFC2865, RFC2716, RFC1759, RFC3580, RFC3748 Extensible Authentication Protocol (EAP) • RFC2571 SNMP Framework • RFC2572 SNMP Message Processing and Dispatching • RFC2573 SNMP Applications • RFC2574 User-based Security Model for SNMPv3 • RFC1981 Path MTU Discovery for IPv6 • RFC2460 IPv6 • RFC2461, RFC4861 Neighbor Discovery for IPv6 • RFC2462, RFC4862 IPv6 Stateless Address Auto-configuration • RFC2464 IPv6 over Ethernet and definition • RFC2767 Dual Stack Hosts using the 'Bump-In-the-Stack' Technology • RFC3513, RFC4291 IPv6 Addressing Architecture • RFC2893, RFC4213 IPv4/IPv6 dual stack function • RFC3484 Default Address Selection for Internet Protocol version 6 • PoE MIB • RFC3621 Power Ethernet MIB • RFC1583 OSPF Version 2 Compatibility

Ordering Information	
Part Number	Description
DGS-3630-28SC/SI	20 SFP ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Standard Image ⁵
DGS-3630-28SC/EI	20 SFP ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Enhanced Image ⁵
DGS-3630-28SC/MI	20 SFP ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with MPLS Image ⁵
DGS-3630-28TC/SI	20 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Standard Image ⁵
DGS-3630-28TC/EI	20 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Enhanced Image ⁵
DGS-3630-28TC/MI	20 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with MPLS Image ⁵
DGS-3630-52TC/SI	44 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Standard Image ⁵
DGS-3630-52TC/EI	44 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Enhanced Image ⁵
DGS-3630-52TC/MI	44 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with MPLS Image ⁵
DGS-3630-28PC/SI	20 10/100/1000BASE-T PoE ports + 4 Combo 10/100/1000BASE-T PoE/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Standard Image
DGS-3630-28PC/EI	20 10/100/1000BASE-T PoE ports + 4 Combo 10/100/1000BASE-T PoE/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Enhanced Image
DGS-3630-28PC/MI	20 10/100/1000BASE-T PoE ports + 4 Combo 10/100/1000BASE-T PoE/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with MPLS Image
DGS-3630-52PC/SI	44 10/100/1000BASE-T PoE ports + 4 Combo 10/100/1000BASE-T PoE/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Standard Image
DGS-3630-52PC/EI	44 10/100/1000BASE-T PoE ports + 4 Combo 10/100/1000BASE-T PoE/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Enhanced Image
DGS-3630-52PC/MI	44 10/100/1000BASE-T PoE ports + 4 Combo 10/100/1000BASE-T PoE/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with MPLS Image
Optional License Upgrades	
DGS-3630-28SC-SE-LIC	DGS-3630-28SC Standard Image to Enhanced Image License
DGS-3630-28SC-EM-LIC	DGS-3630-28SC Enhanced Image to MPLS Image License
DGS-3630-28SC-SM-LIC	DGS-3630-28SC Standard Image to MPLS Image License
DGS-3630-28TC-SE-LIC	DGS-3630-28TC Standard Image to Enhanced Image License
DGS-3630-28TC-EM-LIC	DGS-3630-28TC Enhanced Image to MPLS Image License
DGS-3630-28TC-SM-LIC	DGS-3630-28TC Standard Image to MPLS Image License
DGS-3630-52TC-SE-LIC	DGS-3630-52TC Standard Image to Enhanced Image License
DGS-3630-52TC-EM-LIC	DGS-3630-52TC Enhanced Image to MPLS Image License

DGS-3630-52TC-SM-LIC	DGS-3630-52TC Standard Image to MPLS Image License
DGS-3630-28PC-SE-LIC	DGS-3630-28PC Standard Image to Enhanced Image License
DGS-3630-28PC-EM-LIC	DGS-3630-28PC Enhanced Image to MPLS Image License
DGS-3630-28TC-SM-LIC	DGS-3630-28PC Standard Image to MPLS Image License
DGS-3630-52PC-SE-LIC	DGS-3630-52PC Standard Image to Enhanced Image
DGS-3630-52PC-EM-LIC	DGS-3630-52PC Enhanced Image to MPLS Image License
DGS-3630-52TC-SM-LIC	DGS-3630-52PC Standard Image to MPLS Image License
Optional Management Software	
DV-700-N25-LIC	D-View 7 - 25 Node License
DV-700-N50-LIC	D-View 7 - 50 Node License
DV-700-N100-LIC	D-View 7 - 100 Node License
DV-700-N250-LIC	D-View 7 - 250 Node License
DV-700-N500-LIC	D-View 7 - 500 Node License
DV-700-N1000-LIC	D-View 7 - 1000 Node License
DV-700-P5-LIC	D-View 7 - 5 Probe License
DV-700-P10-LIC	D-View 7 - 10 Probe License
DV-700-P25-LIC	D-View 7 - 25 Probe License
DV-700-P50-LIC	D-View 7 - 50 Probe License
DV-700-P100-LIC	D-View 7 - 100 Probe License
Optional 10 Gbe SFP+ Transceivers	
DEM-431XT	10GBASE-SR Multi-mode, OM1:33M/OM2:82M/OM3:300M (w/o DDM)
DEM-432XT	10GBASE-LR Single-mode, 10 km (w/o DDM)
DEM-433XT	10GBASE-ER Single-mode, 40 km (w/o DDM)
DEM-434XT	10GBASE-ZR Single-mode, 80 km (w/o DDM)
DEM-436XT-BXD	10GBASE-LR Single-mode, 20 km (TX-1330/RX-1270 nm) (w/o DDM)
DEM-436XT-BXU	10GBASE-LR Single-mode, 20 km (TX-1270/RX-1310 nm) (w/o DDM)
Optional 1 Gbe SFP Transceivers	
DGS-712	1000BASE-T Copper SFP Transceiver
DEM-210	100BASE-FX Single-mode, 15 km
DEM-302S-LX	1000BASE-LX Single-mode, 2 km
DEM-310GT	1000BASE-LX Single-mode, 10 km
DEM-311GT	1000BASE-SX Multi-mode, 550 m
DEM-312GT2	1000BASE-SX Multi-mode, 2 km
DEM-314GT	1000BASE-LHX Single-mode, 50 km
DEM-315GT	1000BASE-ZX Single-mode, 80 km
DEM-220T	100BASE-BX-D Single-mode, 20 km (TX-1550/RX-1310 nm) 100BASE-BX-U Single-mode, 20 km (TX-1310/RX-1550 nm)
DEM-220R	100BASE-BX-U Single-mode, 20 km (TX-1310/RX-1550 nm)

DGS-3630 Series Layer 3 Stackable Managed Switches

DEM-302S-BXD	1000BASE-BX-D Single-mode, 2 km (TX-1550/RX-1310 nm)
DEM-302S-BXU	1000BASE-BX-U Single-mode, 2 km (TX-1310/RX-1550 nm)
DEM-330T	1000BASE-BX-D Single-mode, 10 km (TX-1550/RX-1310 nm)
DEM-330R	1000BASE-BX-U Single-mode, 10 km (TX-1310/RX-1550 nm)
DEM-331T	1000BASE-BX-D Single-mode, 40 km (TX-1550/RX-1310 nm)
DEM-331R	1000BASE-BX-U Single-mode, 40 km (TX-1310/RX-1550 nm)
Optional 10 Gbps SFP+ Direct Attach Cables	
DEM-CB100S	10 GbE SFP+ 1 m Direct Attach Cable
DEM-CB300S	10 GbE SFP+ 3 m Direct Attach Cable
DEM-CB700S	10 GbE SFP+ 7 m Direct Attach Cable
Optional Redundant Power Supplies	
DPS-500A	AC Redundant Power Supply
DPS-500DC	DC Redundant Power Supply
DPS-700	AC Redundant Power Supply for PoE models

¹ Depending on the currently used image version, additional Enhanced and MPLS Image features can be accessed by purchasing the appropriate upgrade license.

² Only DGS-3630 Series switches with the same image version can be physically stacked. For example, a DGS-3630 Series switch running the Standard Image can only be stacked with another DGS-3630 Series switch running the Standard Image.

³ For non-PoE models, by default, the fan speed is low. When the temperature inside the chassis exceeds 36 °C (97 °F), the fans switch to high speed until the temperature drops below 33 °C (91 °F). For PoE models, by default, the fan speed is low. When the temperature inside the chassis exceeds 37 °C (98 °F), the fans switch to high speed. When the temperature in the chassis reaches between 22 °C to 27 °C (71 °F to 80 °F), the fans switch to medium speed. When the temperature inside the chassis drops below 22 °C (71 °F), the fans switch to low speed.

⁴ Based on maximum value of Switch Resource Management (SRM).

⁵ Stacking cable and USB flash card not included.

⁶ Supported in firmware revision R2.10.

⁷ OpenFlow Pure Mode is supported by R2.10, OpenFlow Hybrid Mode is supported by R2.20.

⁸ Supported by R2.25

Updated 2022/03/04